


# Platform Scales



- Large backlit LCD display
- Simple 4 button operation
- Portable with battery power
- Kg/ lb/ oz/ lb & oz switchable
- Tare function
- Weighing
- Hold function
- RS-232 bi-directional interface
- Animal / dynamic weighing
- Stainless steel weighing pan with remote indicator
- Mains adapter and wall mounting kit supplied as standard



**Model CPWplus 150**

**Readability 150Kgs @ 50grams**

## **Technical Specifications**

**Models CPWplus: 35, 75, 150, 200**

**Maximum capacity:** 35Kg, 75Kg, 150kg, 200Kg


**Readability:** 10, 20, 50, 50g

**Tare range:** Full

**Repeatability (S.D.):** 50g

**Linearity (±):** 100g

**Platform size:** 300x300mm



## **General Specifications**

**Units of measurement:** Kilogram (kg), Pound (lb), Pound-Ounce (lb-oz)

**Typical stabilisation time:** 2 Sec

**Interface:** RS-232 bi-directional Interface

**Calibration:** Automatic External with user selectable calibration mass

**Display:** LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together

**Operating temperature:** 0° - 40°C

**Housing:** Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform

**Overall dimensions (WxDxH):** 300x300x50mm

**Power supply:** 6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter

**Net weight:** 4kg

## **Key Accessories**

- Hard Carry Case with Lock
- Thermal Printer
- Thermal Paper Roll for Printer
- RS-232 Cable
- DU - Data Collection Programme
- RS-232 Cable



We follow a policy of continuous improvement and reserve the right to change specifications without notice.